



HIGH PERFORMANCE THERMAL TILT AND TURN DOOR
EF1070




FRAME

FRAME DEPTH	70mm (2 ¾")
MIN SINGLE WINDOW WIDTH	483mm (19")
MAX SINGLE WINDOW WIDTH	1000mm (40")
RECOMMEND MAX SINGLE WINDOW WIDTH	813mm (32")
MIN SINGLE WINDOW WIDTH	584mm (23")
MAX SINGLE WINDOW HEIGHT	1980mm (78")
RECOMMEND MAX SINGLE WINDOW WIDTH	1524mm (60")

GLAZING

Insulated, Tempered Glass, Low-E, Argon Filled, Warm-Edge Spacer, 3A Molecular Sieve

Thickness	Double Glazing	5mm+12mm+5mm (OVERALL = 22mm (7/8"))
		6mm+12mm+6mm (OVERALL = 24mm (1"))
		8mm+12mm+8mm (OVERALL = 28mm (1-1/8"))
		5mm+12mm+5mm+12mm+5mm (OVERALL = 39mm (1-1/2"))
Triple Glazing		6mm+12mm+6mm+9mm+6mm (OVERALL = 39mm (1-1/2"))
		6mm+12mm+6mm+12mm+6mm (OVERALL = 42mm (1-5/8"))






ENERFREES
Window & Wall Systems

TILT AND TURN DOOR

S-EF1070

DETAILS:






FENESTRATION

Commonly used in high-rise or mid-rise buildings that meets increased loading requirements and limits on deflection, and in buildings where frequent and extreme use of the fenestration products is expected.

FINISH

POWDER COATED. Powder coating is a polyester based coating that uses uniformly sized micro-beads of polyester, electrostatically charged to adhere to base materials. The coating is thick like an epoxy paint, but because it is electrostatically charged and then baked/cured onto the base material, it doesn't flake or peel like paint or epoxy. The color is softer than comparable colors and the depth of the coating is larger.



ADVANTAGE:

- Wide selection of colours
- Texturized finish is an option

ENERFREES HIGH-PERFORMANCE THERMAL BREAK (PA 66 OR NYLON 66)

Polyamide 66 (PA66) is a type of nylon. PA 66 is made of two monomers each containing 6 carbon atoms, hexamethylenediamine and adipic acid.

Melting point: 268.8 °C
Formula: $(C_{12}H_{22}N_2O_2)_n$
Density: 1.31 g/cm³
Boiling point: 452.1 °C
PubChem CID: 3032893

General Characteristic:

- High strength and stiffness at high temperature
- Good impact strength, even at low temperature
- Good abrasion and wear resistance
- Good fatigue resistance
- High water absorption and water equilibrium content limits the usage
- Low dimensional stability





ENERFREES
Window & Wall Systems

TILT AND TURN DOOR

S-EF1070

FRAME DESCRIPTION:

High Performance Thermally broken window system with frame depth of 70mm (2 ¾") frame section.



PARTS AND ACCESSORIES

<p>WPPFA0001 – PRIME FRAME ASSEMBLE (PFA) 6063-T5</p>	
<p>WPOPA0001 – OUTSIDE PRIME ALUMINUM (OPA) 6063-T5</p>	
<p>WPIPA0001 – INSIDE PRIME ALUMINUM (IPA) 6063-T5</p>	



ENERFREES
Window & Wall Systems

TILT AND TURN DOOR

S-EF1070

<p>WPCTB0001 – C THERMAL BREAK (CTB) NYLON 66 (PA66)</p>	
<p>WPMFA0001 – MULLION FRAME ASSEMBLY (MFA)</p>	
<p>WPOMA0001 – OUTSIDE MULLION ALUMINUM (OMA) 6063-T5</p>	
<p>WPIMA0001 – INSIDE MULLION ALUMINUM (IMA) 6063-T5</p>	
<p>WPSFA0001 – SASH FRAME ASSEMBLY (SFA)</p>	



ENERFREES
Window & Wall Systems

TILT AND TURN DOOR

S-EF1070

<p>WPOSF0001 – OUTSIDE SASH FRAME (OSF) 6063-T5</p>	
<p>WPISF0001 – INSIDE SASH FRAME (ISF) 6063-T5</p>	

GLASS STOPS

<p>WPGSX0001 – GLASS STOP (GSX) 6063-T5</p>	
<p>WPGSX0002 – GLASS STOP (GSX) 6063-T5</p>	
<p>WPGSX0003 – GLASS STOP (GSX) 6063-T5</p>	
<p>WPGSX0005 – GLASS STOP (GSX) 6063-T5</p>	



GLAZING (INSULATED GLASS UNITS) Tempered, Low-E, Argon Filled, Warm-Edge Spacer, 3A Molecular Sieve	
GITPT0039- TRIPLE PANE GLASS (TPG 1 9/16" OA)	<p>5+12+5+12+5MM 39mm [1 9/16"]</p>
GITPT0042- TRIPLE PANE GLASS (TPG 1 5/8" OA)	<p>6+12+6+12+6MM 42mm [1 5/8"]</p>
GIDPT0026- DOUBLE PANE GLASS (DPG 1" OA)	<p>5+16+5MM 26mm [1"]</p>
GIDPT0028- DOUBLE PANE GLASS (DPG 1 1/8" OA)	<p>6+16+6MM 28mm [1 1/8"]</p>
GIDPT0032- DOUBLE PANE GLASS (DPG 1 1/4" OA)	<p>8+16+8MM 32mm [1 1/4"]</p>



ENERFREES
Window & Wall Systems

TILT AND TURN DOOR

S-EF1070

<p>WAGSB0001 - GLASS SETTING BLOCK (GSB) PVC</p>	<p>50mm [1 15/16"] 6mm [1/4"]</p>
<p>WAGSB0002 - GLASS SETTING BLOCK (GSB) PVC</p>	<p>39mm [1 9/16"] 6mm [1/4"] 34mm [1 5/16"] 1mm [7/16"]</p>
<p>WAGSB0002 - GLASS CORNER SETTING BLOCK (CSB) PVC</p>	<p>83mm [3 1/4"] 82mm [3 1/4"]</p>

SEALS

EPDM rubber is a high-density synthetic rubber used for outdoor applications and other spaces in need of tough, versatile parts.

<p>WSIGX0002 - INTERIOR GASKET (IGX) EPDM RUBBER</p>	<p>7mm [1/4"]</p>
<p>WSEGX0005 - EXTERIOR GASKET (EGX) EPDM RUBBER</p>	<p>7mm [1/4"]</p>



ENERFREES
Window & Wall Systems

TILT AND TURN DOOR

S-EF1070

<p>WSESX0007 – EXTERIOR SASH GASKET (ESG) EPDM RUBBER</p>	
<p>WSISX0007 – INTERIOR SASH GASKET (ISG) EPDM RUBBER</p>	

OTHER COMPONENT/S	
<p>WADXX0001 – EXTERIOR DRAIN COVER (DXX) PVC</p>	
<p>WAWBX0001 – WEATHER BAR (WBX) 6063-T5</p>	
<p>WPCKX0001 – CORNER JOINT KEY (CJK) STAINLESS STEEL</p>	



ENERFREES
Window & Wall Systems

TILT AND TURN DOOR

S-EF1070

<p>WPCJB0001 – CORNER JOINT BLOCK D-3/4" (CJB) 6063-T5</p>	
<p>WPCJB0002 – CORNER JOINT BLOCK D-1/2" (CJB) 6063-T5</p>	
<p>WFIFX0001 – INJECTED FOAM INSULATION (IFX)</p>	

PERIMETER EXTENDERS

<p>PFE6X0001 – PF EXTENDER 6063-T5</p>	
<p>PFE6X0002 – PF EXTENDER 6063-T5</p>	



HARDWARE	
ONE-CLICK HANDLE E-HOC HANDLE AND LOCKING SYSTEM	
TILT AND TURN HINGE	
FRICTION HINGE E-FHTB	<p>Technical drawing of the friction hinge (E-FHTB) showing dimensions A through I and a detail view of the hinge tip. The detail view shows a 18mm [3/4"] width, a 16mm [5/8"] height, and a 22mm [7/8"] width at the base.</p>



GENERAL SPECIFICATION

I. PACKAGE INCLUDES

Manufacturing includes labour, materials, and services for the complete fabrication and assembly of EF1070 Tilt and Turn Door System. Fabrication to include all necessary accessories and components, anchors, joint blocks, drain cover, seal rubbers, hardware, and sealants as required in the purchase agreement.

II. PACKAGE EXCLUDES

Structural installation or provision, framing, interior and exterior trims replacement/repairs, concrete masonry, brick restoration, final cleaning, protection, and/or any related work as specified.

III. PERFORMANCE AND QUALITY STANDARD REQUIREMENT AND ASSURANCE

Enerfrees EF1070 Tilt and Turn Door supplied to client under this specification must comply to the performance standard requirements and test report from an independent testing laboratory certifying compliance shall be given upon request by the owner/architect/contractor.

Test Required: AAMA/WDMA/CSA 101/I.S.2/A440-17 NAFS – North American Fenestration Standard / Specification for windows, doors and skylights and A440S1:19 Canadian Supplement to AAMA/WDMA/CSA 101/I.S.2/A440-17 NAFS - North American Fenestration Standard / Specification for windows, doors and skylights.

IV. MANUFACTURING REFERENCES

An approved shop drawing shall be provided for manufacturing reference and Enerfrees pricing. Enerfrees pricing and drawing shall be signed back to finalize manufacturing and fabricating details.

V. ALUMINUM EXTRUSION

All extruded aluminum sections shall be 6063-T5 alloy or equivalent.

VI. FASTENERS

Fasteners shall be stainless steel or as required.

VII. FABRICATION/MANUFACTURING

Tilt and Turn Door will be fabricated according to the approved shop drawings. All joints will be assembled tight using manufactures provided assembly machines to comply with quality standard and assurance to carry out the product design performance.



VIII. INSTALLATION

Enerfrees products that will be installed shall conform with the manufacturer's instructions and should comply with approved shop drawings. The work shall be performed by qualified or certified installer using proper equipment to carry out necessary, proper, and efficient installation in a professional manner.

IX. PROTECTION

Exposed aluminum finished surface shall be protected from contamination of mortar, concrete, paint, mud, soil, grease, sealant or caulking compound, and any other harmful substance that can cause damage to surface finish from prolong adhesion.

X. CLEANING

Provisional cleaning shall perform primary clear-out after installation and final cleaning shall be executed by the project owner in accordance with the general conditions listing methods outlined in AAMA 609 and 610-02.

TILT AND TURN DOOR INTEGRATION TO FIXED WINDOW



Enerfrees EF1070 Tilt and Turn Door is unlimited to integrate different operations and functionality to fixed window with custom sizes within the minimum/maximum width and height limits specified.